



06/10/2014

Ocean Power Technologies PowerBuoy®: System-level Design, Development and Validation Methodology OMAE 2014

Mike Mekhiche

Kathleen A. Edwards James G. Bretl

OPT Proprietary

*Information contained in the presentation may not be used without
the express permission of Ocean Power Technologies, Inc.*

Ocean Power Technologies, Inc.

*1590 Reed Road
Pennington, NJ 08534-5003*

Outline

Objective: Window into design approach at a WEC company

- Describe the product (PowerBuoy)
 - Aspects that design must consider
- Design approach
 - Structure
 - Power Takeoff (PTO)
- Examples drawn from past projects

Company Overview


Commenced Operations:	1994
Incorporation:	Delaware, USA
Operating Locations:	Pennington, NJ, USA; Warwick, UK; Melbourne, Australia
Total Employees:	30
Intellectual Property:	68 US patents issued or pending
Cash and Investments:	\$19.6 million (as of January 31, 2014)
Public Listing:	Nasdaq (OPTT)
Company Focus:	Design, manufacture, sell systems to generate power from ocean waves
Project Locations:	North America, Europe, Japan, Australia

OPT Proprietary



PowerBuoy Description

- Moored system
- Float moves vertically along spar; relative motion drives thrust rod to rack and pinion system. Generator rotates, creating power.
- Power delivered to local payload (“autonomous”) or to grid (“utility”)



Schematic of PowerBuoy for utility project. Compliant mooring not shown.

Stages of Design Process

- Define requirements
- Structure design
 - Concept generation and evaluation
 - Wave tank testing of concepts
 - Down-selection of concepts
- PTO design
 - Concept generation and evaluation
 - Component and subsystem testing

These steps will be illustrated with examples from projects a couple projects that were funded by DOE and internal funding in the following slides

Requirements

- Requirement source
 - Customer generated: preferred but not always possible
 - Internally generated: customer feedback, market research, past experience
- Information included in requirements
 - Performance targets
 - Output power, efficiency, operating voltages and currents, mechanical and electrical interfaces, data monitoring and acquisition
 - Cost targets
 - Define cost metrics
 - Estimate capital and operational costs
 - Physical parameters
 - Weight, volume, transportation considerations
 - Site conditions
 - MetOcean: wave climate, survival conditions, water depth, seabed slope and type
 - Logistics: Deployment, on-site maintenance and support, recovery for service
 - System functions
 - Mechanical
 - Electrical

Example Requirements Document

Document No: SPC-300-0003

Page 2 of 67

Title: PB-Max Functional Specification

Revision: Rev 2

TABLE OF CONTENTS

Table of Contents	2
1 Introduction	6
1.1 Overview	6
1.2 Business Context	6
1.3 Glossary	6
2 General Description	7
2.1 Product / System Core Characteristics	7
2.2 Constraints	7
3 General Requirements Specification	8
3.1 Safety	8
3.1.1 Description	8
3.1.2 Criticality	8
3.1.3 Technical issues	8
3.1.4 Dependency with other requirements	8
3.1.5 Other aspects	8
3.2 Cost of Energy requirements	9
3.2.1 Description	9
3.2.2 Criticality	9
3.2.3 technical issues	9
3.2.4 Dependency with other requirements	10
3.2.5 Other aspects	10
3.3 Design Life Requirements	10
3.3.1 Description	10
3.3.2 Criticality	10
3.3.3 technical issues	10
3.3.4 Dependency with other requirements	11
3.3.5 Other aspects	11



OPT Proprietary

Information contained in the presentation may not be used without the express permission of Ocean Power Technologies, Inc.

7

Proprietary Information

This document & information contained herein is the sole property of Ocean Power Technologies (OPT), & may not be reproduced or used for any purpose other than which it was intended without permission from OPT.

Ocean Power Technologies, Inc. Ocean Power Technologies Ltd
1690 Reed Road, Pennington, New Jersey 08634, USA Warwick Innovation Centre, Gallows Hill, Warwick, CV34 6UW, UK
Unless otherwise specified this document is CONTROLLED only when viewed in the form of electronic media from a CONTROLLED source.
Once printed, it becomes an UNCONTROLLED document & users shall verify the correct revision.

Example Requirements Document



OPT Proprietary

Information contained in the presentation may not be used without the express permission of Ocean Power Technologies, Inc.

Document No:	SPC-300-0003	Page 3 of 67
Title:	PB-Max Functional Specification	
Revision:	Rev 2	
3.4	Manufacturability and Assembly Requirements	12
3.4.1	Description	12
3.4.2	Criticality	12
3.4.3	technical issues	12
3.4.4	Dependency with other requirements	13
3.4.5	Other aspects	13
3.5	Reliability and Availability	13
3.5.1	Description	13
3.5.2	Criticality	13
3.5.3	technical issues	13
3.5.4	Dependency with other requirements	14
3.5.5	Other aspects	15
3.6	Maintenance Requirement	15
3.6.1	Description	15
3.6.2	Criticality	15
3.6.3	Technical Issues	15
3.6.4	Dependency with other Requirements	16
3.6.5	other aspects	16
3.7	Dimensional requirements	16
3.7.1	Description	16
3.7.2	Criticality	16
3.7.3	technical issues	16
3.7.4	dependency with other requirements	17
3.7.5	Other aspects	17
3.8	Water Depth Requirement	17
3.8.1	Description	17
3.8.2	Criticality	17
3.8.3	Technical Issues	17
3.8.4	Dependency with other Requirements	18
3.8.5	other aspects	18
3.9	Operational Survivability Requirements	18
3.9.1	Description	18
<small>Proprietary Information This document & information contained herein is the sole property of Ocean Power Technologies (OPT), & may not be reproduced or used for any purpose other than which it was intended without permission from OPT. Ocean Power Technologies, Inc Warwick Innovation Centre, Gallows Hill, Warwick, CV34 6UW, UK 1690 Reed Road, Pinnington, New Jersey 08634, USA Unless otherwise specified this document is CONTROLLED only when viewed in the form of electronic media from a CONTROLLED source. Once printed, it becomes an UNCONTROLLED document & users shall verify the correct revision.</small>		

Example Requirements Document



OPT Proprietary

Information contained in the presentation may not be used without the express permission of Ocean Power Technologies, Inc.

Document No: SPC-300-0003		Page 4 of 67
Title: PB-Max Functional Specification		
Revision: Rev 2		
3.9.2	Criticality	18
3.9.3	Technical Issues	18
3.9.4	Dependency with other Requirements	19
3.9.5	other aspects	19
3.10	Marine Environmental / regulatory / certification requirements	20
3.10.1	Description	20
3.10.2	Criticality	20
3.10.3	technical issues	20
3.10.4	Dependency with other requirements	20
3.10.5	Other aspects	20
3.11	Transportability and Logistics Requirements	21
3.11.1	Description	21
3.11.2	Criticality	21
3.11.3	Technical Issues	21
3.11.4	Dependency with other Requirements	22
3.11.5	other aspects	22
3.12	Deployment requirements	22
3.12.1	Description	22
3.12.2	Criticality	22
3.12.3	technical issues	22
3.12.4	Dependency with other requirements	23
3.12.5	Other aspects	23
3.13	Water Integrity requirements	25
3.13.1	Description	25
3.13.2	Criticality	25
3.13.3	Technical issues	25
3.13.4	Dependency with other requirements	26
3.13.5	Other aspects	26
3.14	Power Quality Requirement	27
3.14.1	Description	27
3.14.2	Criticality	27
3.14.3	Technical Issues	27

Proprietary Information
 This document & information contained herein is the sole property of Ocean Power Technologies (OPT), & may not be reproduced or used for any purpose other than which it was intended without permission from OPT.
 Ocean Power Technologies, Inc. Ocean Power Technologies Ltd
 1690 Reed Road, Pennington, New Jersey 08634, USA Warwick Innovation Centre, Gallows Hill, Warwick, CV34 6UW, UK
 Unless otherwise specified this document is CONTROLLED only when viewed in the form of electronic media from a CONTROLLED source.
 Once printed, it becomes an UNCONTROLLED document & users shall verify the correct revision.

Example Requirements Document

3.14.4	Dependency with other Requirements	27
3.14.5	other aspects	27
3.15	Quality Requirement	27
3.15.1	Description	27
3.15.2	Criticality	28
3.15.3	Technical Issues	28
3.15.4	Dependency with other Requirements	28
3.15.5	other aspects	29
3.16	System Architecture	30
4	Functional Requirements	30
4.1	PowerBuoy System requirements	30
4.1.1	Hydrodynamic Loads	31
4.1.2	Powerbuoy control algorithm	31
4.2	Mechanical System Requirements	37
4.2.1	Mooring and Fixing system	37
4.2.2	Mechanical PTO system	42
4.2.3	Mechanical Structural system	45
4.2.4	Electrical packaging system	49
4.2.5	Mechanical Locking system	51
4.2.6	Thermal Management system	53
4.3	Electrical System Requirements	54



OPT Proprietary

Information contained in the presentation may not be used without the express permission of Ocean Power Technologies, Inc.

10

Structure Design Overview

- Concept generation and evaluation
- Wave tank testing of concepts
- Down-selection of concepts

Structure: Concept Generation and Evaluation

Example tradeoff of 3 floats and 3 moorings

- Down-selected from wider range of geometries
 - Frequency domain modeling
- Concepts compared based on power output and loads
- Analysis tools
 - Simulations performed with OrcaFlex and/or in-house code (time domain modeling, Matlab)
 - Survival and operational wave tank tests (2 rounds)

		Float		
		Symmetric	Cylinder w/Plate	Rhombus
Mooring	Monopile	Compare: <ul style="list-style-type: none"> * Float power performance * Float load shedding vs. draft * Mooring and float loads * Mooring power performance 		
	Gimbal			
	Tension Leg Platform			

Initial conceptual PowerBuoy configurations

Structure: Initial Concept Evaluation using Model Tools

For Different Floats, Power Prediction (kW) vs. Sea State


H _s (m)	Symmetric					Cylinder w/Plate					Rhombus				
	5-30	5-30	5-30	500-600	420-500	15-55	15-55	30-40	750-1000	510-600	5-30	5-30	5-30	550-750	550-750
5.5															
3.5			180-270		120-210			380-470		200-210			280-370		180-210
2			50-100					150-160					80-140		
1	5-30	5-30	5-30			15-55	15-55	30-40			5-30	5-30	5-30		
	5	6	7	9	12	5	6	7	9	12	5	6	7	9	12
	T _a (s)					T _a (s)					T _a (s)				

For Different Floats, Annual Average Power Prediction (kW) at 3 Deployment Sites

	Float		
	Symmetric	Cylinder w/Plate	Rhombus
Site A	40-90	90-140	110-160
Site B	70-120	90-140	130-180
Site C	90-140	120-190	180-250

Example Survival Load Simulations at Different Wave Periods

Mooring Load for Symmetric Float 1



Structure: Concept Evaluation using Wave Tank Tests


Test Activities

	Test Type	
	Survival	Operational
Test 1	3 Floats 3 Moorings 3 Drafts	3 Floats 3 Moorings 3 Drafts
Test 2	4 Floats 1 Mooring 1 Draft	
Test 3		2 Floats 1 Mooring 2 Controls

Operational Test: Model Installation




Survival Test: Wave Calibration




- Operational tests
 - Evaluate power performance, fatigue
 - Tune hydrodynamic coefficients
- Survival tests
 - Estimate design loads
 - Tune hydrodynamic coefficients
- Tuned simulations used for post-test analysis

Simulation with Test-Tuned Coefficients



Example Simulation Evaluation



OPT Proprietary

Information contained in the presentation may not be used without the express permission of Ocean Power Technologies, Inc.

Structure: Down-Selection of Concepts

- Compare floats
 - Highest power for Rhombus
- Compare moorings
 - Highest power output for Monopile
 - Lowest loads for Tension Leg Platform
- Final decision then made by management based on these and other considerations (e.g. cost, deployment, customer preference)
- On to next stages of project

			Float		
			Symmetric	Cylinder w/Plate	Rhombus
Mooring	Monopile	Site A	40-90	90-140	110-160
		Site B	70-120	90-140	130-180
		Site C	90-140	120-190	180-250

Comparison of Moorings

Monopile	<p><u>Pro</u> Highest power configuration of all cases studied; 600-610 kW mechanical power Best agreement between predicted and measured</p> <p><u>Con</u> Large float size Estimated base moments (-5.5m survival) 550-750 MN.m @ 40m depth 750-1000 MN.m @ 50m depth Float moment: 40-100 MN.m</p>
TLP	<p><u>Pro</u> Second highest power studied Avoid base moment load</p> <p><u>Con</u> Large float size High tether loads (15-60 MN) @ maximum operating sea state</p>

PTO Design Overview

- Concept generation and evaluation
- Component and subsystem testing

PTO: Concept generation and evaluation

Tradeoff: Rack and Pinion vs. Belt Drive


- Table: Compatibility with PTO
- Other criteria (cost, reliability)
- Vendor input on designs; cost quotes

Winning concept (RP#2) built, tested, validated for ocean deployment


		RP#1	RP#2	Belt #1	Belt#2
		Adjustable input rod	Fixed input rod	External rack on spar	Internal rack in float
		Option?	Option?	Option?	Option?
Input Rod	Fixed Input Rod	✗	✓	✗	✓
	Wire Rope Adjustable Input Rod	✓	✗	✗	✓
Speed Inserter	Gearbox	✓	✓	✓	✓
	Beltbox	✓	✓	✓	✓
	Chain drive	✓	✓	✓	✓
Brakes	External linear brake	✓	✓	✓	✓
	Rotary spar to sheave	✓	✗	✗	✓
	Internal linear rod lock	✓	✓	✗	✓
	Internal rotary pinion caliper brake	✓	✓	✓	✓
Locking Mechanism	Latch	✓	✓	✓	✓
	Shear pin	✓	✓	✓	✓
Pinion	Vendor 1	✓	✓	✓	✓
	Vendor 2	✓	✓	✓	✓
Wire Rope	Vendor 1	✓	✗	✗	✓
	Vendor 2	✓	✗	✗	✓

PTO: Component and Subsystem Testing


- Generator/drive back-to-back test
 - Measurements: Power, thermal performance, motor constants (K_t , K_e)
- Active Front End (AFE) Inverter test
 - Validate interface between High Voltage DC bus and AC voltage on the Utility grid
 - Validate AFE control setup (precharge, synchronization, bidirectional power transfer)
- PTO endurance test
 - Represent real wave conditions
 - Measure efficiency, vibration
 - Validate control, HMI



Setup For Back-to-back Testing of Generator Drive



AFE Subsystem Test Setup



PTO Endurance Test Setup



OPT Proprietary

Conclusions

- Goal: Window into design process for wave energy converters
- Reviewed design process; examples from recent project
- Stages of design process
 - Concept generation and evaluation
 - Testing