

# Design and Validation of a Hybrid Model Testing Setup for Scaled Energy Converters in the NREL Wave Tank

---

Nora Riedinger

Coauthored by Stephen Chamot, Hannah Ross, Rafael Mudafort, Will Wiley, Mark Murphy, Senu Sirnivas, and Matthew Hall

*National Renewable Energy Lab (NREL)*

# Hybrid Model Testing at SWEL



# Background

- 14 meters long, 2.5 meters wide, 1.3 meters deep
- Flap-type 2D wave generator
  - 0.2 meter amplitude
  - 0.5-5 second periods
- Qualisys optical tracking
- FRM1Q floating platform<sup>1,2</sup>

<sup>1</sup>Wiley et al. (2023) <sup>2</sup>Neary et al. (2014)




Photo by Joe DelNero, NREL 70306





Photo by Gregory Cooper, NREL 98911

# Hybrid Model Testing in Wave Tanks




Real-time hybrid model testing of a floating wind platform for extreme marine environments.

*Photo from SINTEF (2016)*



Hybrid model test with multi-propeller actuators at UI Hydraulics Wave Basin Facility.

*Photo by Senu Sirnivas, NREL*




DeepCwind semisubmersible in wave basin with cable-based hybrid coupling.


*Photo from Hall (2016)*




# Hybrid Model Test Setup




# Physical Hardware



1



3



2



# Floating Tidal Turbine



# Full Tank Setup



Photo by Senu Sirnivas, NREL

# Controls Overview

## Tension Control



- Generates pretension
- Distributes wrench between winches

## Feedforward Control



- Speeds up rise time
- Anticipates the motion required to achieve desired force


## Motion Accommodation



- Computes velocity
- Allows floating body to move freely




# Results: Zero Prescribed Wrench



# Results: Wave Case with Small Prescribed Wrench

Phase shift and deviation from desired force




# Challenges

## Addressed:

- Accuracy of underwater pulley placement and measurement
- Access to underwater hardware after installation

## Additional:

- Oscillations about tension set point
- Friction in underwater pulleys
- Additional noise from motion accommodation



# Conclusions

- System hardware designed, tested, and deployed
- Preliminary full system tests performed
- Errors identified and addressed
- Additional issues outstanding
- Expands the testing capabilities at SWEL



*Video by Senu Sirnivas, NREL*

# Future Work

Improve controller to  
achieve wrench within 5%  
RMS of desired values

Integrate  
control system  
with OpenFAST

Install 2 additional  
winches for control  
in 6 DOFs

Test other scaled marine  
energy converters and  
floating platforms



# References

M. Hall, “Hybrid Modeling of Floating Wind Turbines,” Ph.D. dissertation, Dept. Mech. Eng., Univ. of Maine, Orono, ME, 2016. [Online] Available: <https://digitalcommons.library.umaine.edu/etd/2477>

V. S. Neary et al., “Methodology for Design and Economic Analysis of Marine Energy Conversion (MEC) Technologies,” Sandia National Laboratories, Albuquerque, New Mexico, SAND2014-9040, March 2014.

“Water Research: Wave Tank,” NREL, <https://www.nrel.gov/water/wave-tank> (10 April 2025)

W. Wiley, H. Ross, A.K. Sundarrajan, and T.T. Tran, “Design and Modeling of an Open-Source Baseline Floating Marine Turbine” in *University Marine Energy Research Community Conference*, Durham, New Hampshire, United States, 2023.

# Thank You!

---

[www.nrel.gov](http://www.nrel.gov)

This work was authored by the National Renewable Energy Laboratory for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by the U.S. Department of Energy Water Power Technologies Office under the Powering the Blue Economy portfolio. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government. The U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes. This work was supported in part by the U.S. Department of Energy, Office of Science, Office of Workforce Development for Teachers and Scientists (WDTS) under the Science Undergraduate Laboratory Internship (SULI) program.

