

Testing the Tfl SeaSpring, a potential route to lower cost moorings for marine energy devices

Philipp Thies, Stuart Walker, Peter Halswell, Conor Casey, Paul McEvoy

Associate Professor in Renewable Energy

P.R.Thies@exeter.ac.uk

18th October 2022









The TIGER project

TIGER (Tidal Stream Industry Energiser) is the largest ever Interreg project

- The project brings together developers, academia and industry to drive the sector forward
- Through TIGER, we tested the Tfl SeaSpring for Orbital Marine Power

CAMBRIAN

ORBITAL

PLYMOUTH

SE DEOM



Interreg

European Regional Development Fund

France (^{Channel}) England



EXETER

UOS:

EMEC

CATAPULT

MHE NORBINAN

€Minesto



Nonnetia / San Sahaetián 2022

edf

U.,



Mooring Systems

- Floating tidal stream turbines are installed in the highest flow areas
- Mooring systems are critical to the success of the deployment
- Moorings must be designed for peak load conditions
- Conventional designs are heavy and expensive













Mooring system example: Orbital O2

Each mooring line is composed of 225m of studlink chain (56.5 t)



Mooring dampers could reduce peak loading, allowing reduced chain mass, thus reducing:

- Cost (CapEx and OpEx)
- Device loads
- Carbon footprint









Technology from Ideas (Tfl) SeaSpring

- SeaSpring comprises a series of compressive polymer springs linked by chain
- Polymer springs act in tension and provide a tailored, non-linear force response
- As the system is loaded, the polymer
 compresses by up to 50% of its length,
 dissipating mooring line forces and reducing
 fatigue and peak loading
- These load reductions allow for CAPEX and
 OPEX savings by reducing mooring line length
 and weight and reducing maintenance
 requirements













Dynamic Marine and Component test facility (DMaC)

Purpose-built test rig for offshore marine components:

- Tension/compression: 200kN
- Pitch / roll: 10kNm
- Bending: 10kN
- Wet and dry
- Data logging and CCTV
- Common testing:
 - Mooring systems
 - Power cables & Ancillaries
 - Sensors












Test plan

- Force response tests: full cycle and sub-cycle regimes
- Standard operational and 50-year return period storm sea states
- Durability: thousand cycle load level (TCLL) tests at 6 load values (50% -





Installation











France (^{Channel}) England European Regional Development Fund

Test runs














University of Exeter

Test runs












University of Exeter

Results









Results

- Accurate replication of target loads and deflections to within 1%
- SeaSpring device met or exceeded all test targets
- Cyclic force response was measured, and the spring was subjected to aggressive storm sea states
- 5 years of accelerated fatigue was achieved over 2 days' durability testing














Conclusions: Cost-reduction potential

- Previous testing demonstrated
 50% load reduction
- Component testing reduces risk of innovations / critical parts for developers such as Orbital Marine Power
- 50% load reduction allows a reduction in mooring system mass from 226 t to 106 t, driving reduction in cost









Questions

Philipp Thies P.R.Thies@exeter.ac.uk

<u>TIGER: Tidal Stream Industry Energiser</u> project (interregtiger.com)

Or see as at our stand #24

